











STARDUCT INSULATED FIRE DAMPERS RESUME

Website link to download : <https://starduct.vn/en/fire-dampers-fdmfd-c-134>

No.	PICTURES	MODEL NUMBER	Type	DIMENSION (W x H x L) mm		OPERATING TYPE		E&I&S RATING	Leaage Rating	TEST STANDARD	FIGURE TESTING	FAIL SAFE
				SINGLE MODULE	EXTENDED	FUSE LINK	ACCTUATOR		m3/h/m2			
1		S-MFSD	NORMAL OPEN	1200 x 800 x 600			BELIMO UL55 FAIL SAFE SFLF-S-US	120	<200	ISO 10924-1/2	1	Yes, Spring Return
2		S-MFSD	NORMAL OPEN	2000 x 1000 x 600			BELIMO UL555 FAIL SAFE SFNF-S-US	120	<200	ISO 10924-1/2	1	Yes, Spring Return
3		S-MFSD	NORMAL OPEN		W : NO LIMITED Hmax : 1680 L: 600		BELIMO UL55 FAIL SAFE SFLF-S-US	120	<200	ISO 10924-1/2	1	Yes, Spring Return
4		S-MFSD	NORMAL OPEN	1200 x 800 x 210			BELIMO UL55 FAIL SAFE SFLF-S-US	120	<200	ISO 21925-1/2	5&6	Yes, Spring Return
5		S-MFSD	NORMAL OPEN		W : NO LIMITED Hmax : 1928 L: 210		BELIMO UL55 FAIL SAFE SFLF-S-US	120	<200	ISO 21925-1/2	5&6	Yes, Spring Return
6		S-FSD	NORMAL OPEN	1200 x 800 x 210		Mechanical operation with Fuse and torque Linkage		120	<200	ISO 21925-1/2	5&6	Yes, Hand Return
7		S-FSD	NORMAL OPEN		W : NO LIMITED Hmax : 1928 L: 210	Mechanical operation with Fuse and torque Linkage		120	<200	ISO 21925-1/2	5&6	Yes, Hand Return
8		S-FSS	NORMAL OPEN	500 x 500 x 210		Mechanical operation with Fuse and torque Linkage		120	<200	ISO 21925-1/2	1	N
9		SAFD-H	NORMAL OPEN	1200 x 800 x 210			BELIMO MODULATING FAIL SAFE BFN24-SR	60	<360	ISO 21925-1/2	1	Yes, Spring Return
10		SAFD	NORMAL OPEN	800 x 1200 x 210			BELIMO UL55 FAIL SAFE SFLF-S-US	30	<360	ISO 21925-1/2	1	Yes, Spring Return